

5.1

$$\begin{aligned} a &= (-2, 0, 0, 1), \\ b &= (5, 0, 3, 4). \end{aligned} \tag{1}$$

a) To find out if a is timelike, spacelike, or null-like, we compute $a^2 = a \cdot a = a_\mu a^\mu$.

$$a^2 = \eta_{\mu\nu} a^\mu a^\nu = -(-2)^2 + 1^2 = -3 < 0, \tag{2}$$

thus a is timelike. For the case of b ;

$$b^2 = -5^2 + 3^2 + 4^2 = -25 + 9 + 16 = 0, \tag{3}$$

so b is null-like (lightlike).

b)

$$a - 5b = (-2 - 25, 0, -5 \cdot 3, 1 - 5 \cdot 4) = (-27, 0, -15, -19) \tag{4}$$

c)

$$a \cdot b = \eta_{\mu\nu} a^\mu b^\nu = 10 + 4 = 14 \tag{5}$$

5.3

$$\frac{dx}{dt} = V, \quad x(0) = 0. \tag{6}$$

We wish to express x^μ as a function of the proper time τ . We use the relation

$$c^2(d\tau)^2 = (cdt)^2 - (dx)^2, \tag{7}$$

and this gives us

$$\begin{aligned} c^2(d\tau)^2 &= (c^2 - v^2) (dt)^2 \\ &= \left(\frac{c^2}{v^2} - 1 \right) v^2 (dx)^2 \end{aligned} \tag{8}$$

so

$$\frac{dt}{d\tau} = \frac{1}{\sqrt{1 - \frac{v^2}{c^2}}}, \tag{9}$$

$$\frac{dx}{d\tau} = \frac{v}{\sqrt{1 - \frac{v^2}{c^2}}}. \tag{10}$$

$$\tag{11}$$

We integrate this up, and choose $t(\tau = 0) = 0$, in order to obtain:

$$t(\tau) = \frac{\tau}{\sqrt{1 - \frac{v^2}{c^2}}} = \gamma\tau, \tag{12}$$

$$x(\tau) = \frac{v\tau}{\sqrt{1 - \frac{v^2}{c^2}}} = v\gamma\tau. \tag{13}$$

5.4

The four-velocity is given by

$$u = (\gamma, \gamma \mathbf{V}) . \quad (14)$$

The four-acceleration is defined by

$$a = \frac{\partial u}{\partial \tau} . \quad (15)$$

We will now express this in terms of the three-velocity $\mathbf{V}$ and the three-acceleration $\mathbf{A} = \frac{\partial \mathbf{V}}{\partial t}$. The first step is to change derivation variable and then apply the product rule for differentiation:

$$a = \frac{\partial t}{\partial \tau} \frac{\partial u}{\partial t} = \gamma (\dot{\gamma}, \dot{\gamma} \mathbf{V} + \gamma \mathbf{A}) . \quad (16)$$

We also need to calculate $\dot{\gamma}$:

$$\dot{\gamma} = \frac{\partial \gamma}{\partial t} = \frac{\partial}{\partial t} (1 - \mathbf{V}^2)^{-1/2} = \gamma^3 \frac{-2\mathbf{V} \cdot \mathbf{A}}{-2} = \gamma^3 \mathbf{V} \cdot \mathbf{A}, \quad (17)$$

and we are done.

Next, we will compute the inner product of a and u :

$$a \cdot u = -\gamma \dot{\gamma} + \dot{\gamma} \gamma \mathbf{V}^2 + \gamma^2 \mathbf{V} \cdot \mathbf{A} . \quad (18)$$

Insertation of the explicit expression for $\dot{\gamma}$, enables us to write

$$a \cdot u = \gamma^2 \mathbf{V} \cdot \mathbf{A} (-\gamma^2 + \gamma^2 \mathbf{V}^2 + 1) = \gamma^2 \mathbf{V} \cdot \mathbf{A} [\gamma^2 (-1 + \mathbf{V}^2) + 1] = 0 . \quad (19)$$

The two four-vectors are orthogonal.

5.6

a) The velocity is given by

$$V_x = \frac{dx}{dt} = \frac{gt}{\sqrt{1 + g^2 t^2}} \quad (20)$$

As $|gt|$ is always less than $\sqrt{1 + g^2 t^2}$, the speed never exceeds 1; the speed of the light. The speed of the particle approaches this as $t \rightarrow \infty$.

b) According to Hartle, the four-velocity is given by

$$u = (\gamma, \gamma V_x \mathbf{i}), \quad \gamma = \frac{1}{\sqrt{1 - V_x^2}} \quad (21)$$

It would be nice to simplify this expression. To do this, we take a closer look at γ :

$$\gamma = \sqrt{\frac{1}{1 - V_x^2}} = \sqrt{\frac{1}{\frac{1+g^2 t^2}{1+g^2 t^2} - \frac{g^2 t^2}{1+g^2 t^2}}} = \sqrt{1 + g^2 t^2} . \quad (22)$$

The four-velocity can then be written

$$u = (\sqrt{1 + g^2 t^2}, gt \mathbf{i}) . \quad (23)$$

c) Using the zero component of the four-velocity, we can derive an expression for the proper time τ :

$$\frac{dt}{d\tau} = \sqrt{1 + g^2 t^2} \implies \int_{t_0}^t \frac{dt'}{\sqrt{1 + g^2 t'^2}} = \int_{\tau_0}^{\tau} d\tau'. \quad (24)$$

The above integral is a standard integral, which can be evaluated by substitution; set $t = \frac{1}{g} \sinh u$. (check this!) The result is

$$\tau = \frac{1}{g} \sinh^{-1}(gt), \quad (25)$$

where we have defined a coordinates such that $t_0 = \tau_0 = 0$. The four-velocity can now be expressed in terms of the proper time:

$$u = (\cosh(g\tau), \sinh(g\tau)\mathbf{i}) \quad (26)$$

Next, we also wish to derive an expression for x as a function of the proper time. This is simple at this point, we apply the expression for the three-velocity:

$$\frac{dx}{d\tau} = \sinh(g\tau) \implies x = \frac{1}{g} \cosh(g\tau) + x_0. \quad (27)$$

Setting $x(0) = 0$, this becomes $x = \frac{1}{g} [\cosh(g\tau) - 1]$.

d) Using relation (5.41) in Hartle, we find the four-momentum :

$$p = mu = (m \cosh(g\tau), m \sinh(g\tau)\mathbf{i}) \quad (28)$$

The four-force is then

$$u = \frac{dp}{d\tau} = \left(\frac{m}{g} \sinh(g\tau), \frac{m}{g} \cosh(g\tau)\mathbf{i} \right). \quad (29)$$

The three-force is given by

$$m \frac{d}{dt} \frac{d\mathbf{x}}{dt} = m \frac{g}{\sqrt{1 + g^2 t^2}} \mathbf{i} - \frac{g^3 t^2}{(\sqrt{1 + g^2 t^2})^3} \mathbf{i} = \frac{m}{g\gamma} \left(1 - \frac{g^2 t^2}{\gamma^2} \right) \mathbf{i}. \quad (30)$$

5.7

We first look at the four-force exerted in the instantaneous rest frame (with proper time τ) of the particle. (we neglect the $\mathbf{i}$ in this exercise). It is given by

$$f' = (0, mg) \quad (31)$$

As this is a four-vector it can be Lorentz-transformed

$$f_\mu = L_{\mu\nu} f'_\nu, \quad (32)$$

and we get

$$\begin{aligned} f &= (-\sinh \theta, \cosh \theta mg) \\ &= \left(\gamma \frac{dx}{dt} mg, \gamma mg \right). \end{aligned} \quad (33)$$

The generalization of Newton's law is

$$m \frac{du}{d\tau} = f, \quad (34)$$

where $u = (\gamma, \gamma \frac{dx}{dt})$ is the four-velocity. For the spatial component this yields

$$\frac{d}{d\tau} \gamma \frac{dx}{dt} = \frac{d}{d\tau} \frac{dx}{d\tau} = \gamma g. \quad (35)$$

We wish to solve this for x expressed in terms of τ , we should thus find an expression for γ , which does not depend on t :

$$\begin{aligned} \frac{1}{\gamma^2} &= 1 - \left(\frac{dx}{dt} \right)^2 = 1 - \frac{1}{\gamma^2} \left(\frac{dx}{d\tau} \right)^2 \\ \Rightarrow \gamma &= \sqrt{1 + \left(\frac{dx}{d\tau} \right)^2} \end{aligned} \quad (36)$$

We now return to (35) and write $\frac{dx}{d\tau} = V$:

$$\frac{d}{d\tau} V = g \sqrt{1 + V^2} \Rightarrow \int \frac{dV}{\sqrt{1 + V^2}} = g \int d\tau \quad (37)$$

This integral is straightforward to evaluate (using $v = \sinh z$), and the result is

$$v = \sinh g\tau, \quad (38)$$

where we have chosen τ such that $V(0) = 0$. Integration with respect to τ , gives us

$$x = \frac{1}{g} [\cosh(g\tau) - 1]. \quad (39)$$

Here we have chosen coordinates such that $x(0) = 0$. For γ we now have

$$\gamma = \sqrt{1 - V^2} = \cosh g\tau = \frac{dt}{d\tau}. \quad (40)$$

Integrating this, we get

$$t = \frac{1}{g} \sinh(g\tau) \quad (41)$$

The equation for the world-line $x(t)$ is found by plugging (41) into (39)

$$x = \frac{1}{g} \left[\sqrt{1 + \sinh^2 g\tau} - 1 \right] = x = \frac{1}{g} \left[\sqrt{g^2 t^2 + 1} - 1 \right]. \quad (42)$$

The world-line is plotted in Fig. 1.